

NEPTUNE POWER-D Switchboards

THE MASTER PIECES :

- v Thyristor Controlled Harmonic Filtration Panels
- v Automatic Power Factor Correction Panel
- v PLC Based DG synchronising Panels & AMF Panels.
- v Power Control Centres & MCCs
- v Feeder Pillar
- v Distribution Boards
- v Mibile Power Distribution Assemblies & Construction Panels









The beginning of it all

Group company NEPTUNE SYSTEMS PVT. LTD. is engaged in manufacturing of custom build panels since 1993. In fact it was one of the first few companies to introduce powder coating on the panels. It has since come a long way and has improved upon designs and quality standards.

The spark of innovation

The world moves on & with the approach of every new era. there is a technical revolution-Development of new ideas - that could not be stopped. To keep pace with all modern electrical, technical developments & introduce them in their right technical aptitude perfection & details of operation is what NEPTUNE desired.

Continuity

Continuity also demands vision. Vision is the basis for the endeavor & solutions that are hardly possible otherwise. Our visionary potential can be found in our technical team, who have put their expertise to test in the production & marketing facility, co-ordinating activities among its various marketing representative offices all over India, with headquarters in New Delhi.

Design and Construction

The panels are manufactured with best quality CRCA sheet steels for lasting strength and the fine finish, Panels offered are standardized, truly boalted with complete modularity in design. The bolted structure is formed by joining various members & the section thus formed is bolted to adjoining structure. Various sizes of feeders can be achieved by fixing the horizontal partition plates at the already punched holes at regular interval. Mounting plate can be adjusted to any depth to accommodate the switchgear and accessories.

Panels manufactured have been successfully type tested at CRPI, Bhopal for short circuit test current of 65 KA for 1 second.

Processing and Painting

The fabrication of the different articles of the panel is carried out on advanced CNC turret punching press and CNC press brake. All the modular parts and sections are subject to eight tank process to ensure anti-rust conditioning, smooth finish and protection against corrosive atmosphere. High quality powder coating is then applied using the latest Swiss machines.

Quality Standards and Testing

Each of the raw material is duly inspected and high quality standards are maintained in manufacturing assembly and testing process by providing adequate resources and reviewing our Quality Management Systems to achieve continual improvements.

Our path to the future

Neptune believes towards extensive expertise in materials & methods which are at full disposal to our customers, because "Trust of our customer is important to us". Success is always the sum of performance & ability. "Performance" that certainly convinces the client & the "Ability" is acknowledged by the market. The basis is provided by our management that has never lost the sight of practicality & has centred its attention on creativity & absolute team spirit of everyone involved in the organisation.

You can depend on us

The combination of vision, innovation, precision & man-power has made us strong. Our customers appreciate our solid reliability & proverbial flexibility when it comes down to supplying even the most complicated solutions economically & on schedule



POWER-D at a Glance

General

- Fully bolted structure
- Ease of handling, transportation and maintenance
- Easily extensible on either side, makes the enclosure future proof.
- Single front & space saving double front can be constructed
- Type of Construction up to Form-4b
- Appropriate level for degree of protection (special design available for higher levels of protection)
- Doors can be hinged on either side offering greater flexibility to configure the panel as per the site conditions.
- Standard sizes available off the shelf, thus cutting down lead time and inventory carrying cost.
 NEPTUNE POWER-D SWITCHBOARD

Automatic Power Factor Correction Panel

- Complete Modular
- Fault Level upto 65 KA for 1 Sec.
- Technical Collaboration with Ducati energia, SPA Italy
- Contactors as well as Thyristor Switching
- Harmonic Block Reactor to suppress the Harmonic in System
- Compact in design

1 2 7

- Proper Natural / Forced air cooling system
- Data Logging facility through RS 485 common part.
- Power Range 25 KVAR 2500 Kvar

PLC Based Synchronic panels

1

- Fault level upto 65 KA for 1 Sec.
- Mimic diagram provided
- Each panel is provided with plastic drawing pocket to keep relevant documents
- Thermostat controlled Space Heater and Cooling Fan provided
- Panel illumination lamp provided











165

.....

1

Feeder Pillars & Distribution Boards

- Construction of panel up to IP 55 / IP 65
- Floor/Wall mounted type
- Suitable for outdoor applications
- PP Powder Coating for outdoor applications
- Provided with Earth Leakage Circuit Breakers, if required

PCC Panels

- 🖙 Fixed & Semi Draw Out type design.
- Fault Level upto 65 KA for 1 Sec.
- Spacious arrangement for cable termination.
- Perforated sheet shroud to Main Horizontal Bus Bar chamber to cater heat dissipation of panel



MCC Panels

- Manual as well as Auto Control
- Provision for BMS compatibility
- Each panel is provided with plastic drawing pocket to keep relevant documents
- Spacious arrangement for cable termination
- Spare terminals provided
- Perforated sheet shroud to Main Horizontal Bus Bar chamber to cater heat dissipation of panel

ELSTEEL Techno Modular Enclosure System

ELSTEEL Techno Modular Enclosure System

IP65 Distribution Boxes

- We manufacture the best steel / GI boxes in the world. They are made as a fully welded construction with grounded and smooth corners, dust and waterproof, to comply IP 65 standard.
- The pretreatment is FE-phosphating and chrome passivation followed by a hybrid powder coating epoxy/polyester, which gives a high corrosion protection.
- Textured powder coated finish (RAL 7032) IP65
 Test Certified Aluminium zinc mounting plates
 Concealed hinge

Technical Data

Rated Operation Voltage : 415 V/690 V AC

3 Phase, 50 Hz **Rated Frequency** : 50 Hz Rated Current : Up to 5000 Amp. Rated Service Voltage : 500 V/690 VAC Short Circuit Level : Upto 65 KA for 1 Sec. Degree of Separation/ : Form-1 to Form-4b Construction Modularity in functional : In steps of 25 mm Unit : Aluminium/Copper **Busbars Busbar Supports** : SMC/DMC/FRP **Degree of Protection** : Upto IP 65 Standard Compliance : IS8623, IS2147 IEC 60439














Partial List of Major Clients

- 🖙 Delhi International Airport
- Delhi Metro U/G Stations
- Delhi Airport Metro Express Line
- Kapurthala Coach Factory
- Indira Gandhi Stadium (Delhi)
- Parliament House (Delhi)
- 🖙 Karni Singh Indoor Stadium
- Container Corporation of India
- Honda Motorcycle & Scooters
- Reliance Energy Ltd.
- Schneider Electric
- Shriram Piston & Rings
- Vardhman Spinning & Mills

- Abhishek Industries
- 🖙 Anrak Aluminium
- Philips Electrical India Ltd.
- Railtel Corporation
- 🖙 Arshiya International
- 🖙 Tata Engineering
- Times of India
- 🖙 Embassy of Qatar
- Australian High Commission
- 🖙 Mughal Sheraton, Agra
- 🖙 The Imperial, Delhi
- Taj Usha Kiran, Gwalior
- EMAAR-MGF

- PGCILGOA(L&T)
- IRCON International
- 🖙 RITES Ltd.
- BPCL (Noida)
- Cummins India Ltd.
- CPWD
- 🖙 ABBLtd.
- r L&⊤Ltd.
- 🖙 Bank of America
- 🖙 Wipro Ltd.
- 🖙 GECapital
- 🖙 Jay Bharat Maruti
- ☞ JT Metro, Dubai



Certifications

		C20
Central Power Research Institute		the Cortificato
SWITCHGEAR TESTING & DEVELOPMENT STATION	Central Power Research Institute SWITCHOURA TISTING & DEVILOPMENT STATION OOVINDPURA BIOPAL-40233. NDIA	Certificate
Phone: +91(0) 755 2586682 Fax: + 91(0) 755 2587774	Phone: +91(0) 755 2586682 Fax: + 91(0) 755 2587774	of Registration
PROVISIONAL REPORT 2 9 AUG 2007	PROVISIONAL REPORT 2 9 AUG 2007	WWW of Registration
eport No.S2070553 Date of test : 27.08.07	Test Report No.82070552 Date of test : 27.08.07	of negistration
Client: Mis Neptane Systems Pvt. Ltd., Nolda Equipment tested: L.T.Switch Board	Client: Mis Neptune Systems Pvt. Ltd., Noida Equipment tested: 800 A L.T.Paret	
Serial Number: 4. Sample Code Nucl. All Datases Board	 Stridt Number: 159A1 Asample Code Nu.: STDSST20751436 Type: LT proal Designation: PCC Panel/Neptone brand) Desning Number: NSPLSTC101 Brand Stridt Stridt Rev:00 short 1 of 5, NSPLSTC101 Brand Stridt 	QUALITY MANAGEMENT SYSTEM - ISO 9001:2008
Drawing Number: NSPL/CPR/01 sheet 1 of 3 NSPL/CPR/01 make an 3/ NSPL/CPR/01 sheet 3 of 3, (Drawings are to be revised & verified)	of 5.NSPL/STC/101 Rev.00 sheet 3 of 5.NSPL/STC/101 Rev.00 sheet 4 of 5.	
Rating of the Equipment: Rated Voltage : 415V 7.2 Rated Current : 4000 A	NSPL/STC101 Rev.00 sheet 5 of 5, 7. Rating of the Equipment:	This is to certify that:
Rated short time current: 65 kArms for 1.0 sec. with initial peak of 143 kA Rated short time current: 65 kArms for 1.0 sec.	7.1 Rated Voltage 1 415/440 VAC 7.2 Rated Current 1 800 A 7.3 Rated Insulation voltage 1 660 V	
Rated mart time currents. Or Journal of the second	7.4 Rated short time current: 50 kArms for 1.0 sec. with initial peak of 105 kA	Neptune Group
Short time current: 65 kArms for 1.0 sec. with initial peak of 143 kA	Equipment tested for the following ratings: K3 Valtage (415440 VAC K2 Carrent: 800 A Basilian valtage (600 V	(Comprising Neptune (India) Limited and Neptune Systems Pvt. Ltd.)
Specification todowed: As per cl. a.2.7 or toology of an optimized	8.4 Short time current: 50 kArms for L0 sec. with initial peak of 105 kA 7 Type of test curried out: Verification of short circuit withstaal strength	A-11. Sector 59
R Y B in second current for	Fype wir tool tuerrend own Verritication of interference wirstand american Specification followed: As per cl. 8.2.3 of 15:3623 (Pan-1), 1993 Test results:	NOIDA 201 301
0553.502 84.16/40.17 1.0 40.17 0553.502 84.16/40.17	Oscillegram Neert time current in kApickArms Doration Equivalent No. R V B in second current for	Gautam Budh Nagar
	52070552.502 51.40 106.0/51.88 50.28 1.0 51.88	Uttar Pradesh India
reations: No absormality. Fine wire fuse intact. All busbars and supports intact. After short circuit test the sample withstood HV test at 2.5 kVress for one minute as	((Three phase test conducted on main bashar consisting of HBB+VBB) \$2070552.804 64.8/20.68 1.0 30.68	
per standard.	(Single phase test conducted on neutral & nearest phase main bushar of HBB+VBB) Observations: Ngrifforemality. Fine wire fuse intact. All bushars and supports. intact.	
1	Remarks Other short circuit that the sample withoused HV test at 2.5 kVenus for one minute as per standard.	Holds Certificate No: FM 70945
AT ENGINEER	TENE INGENER LABORATORY, IN SHARE	and operates a Quality Management System which complies with the requirements of ISO 9001:2008 for the following scope:
Englishing Office		
is only a provisional Support. The field report another another program and there means will be transfed separately within one meanly from the date of MPUTS Forget segments determined in Constant Provise Research Institutes. Beneticset within the Second Secon	This is only a provisional report. The final report atomposite drawings and antigraph entring Officer documents will be install apprenticly within one result, from the date of (highly). Suppose any expression determines	 The design, manufacture and supply of L.T. power & control panels & capacitor
Websharts Tenting & Development Maxim History (1) - NACH, 462023	Residence solution and feature and Residence solution and features form	panels; and II. Marketing of electrical energy management & distribution products.
	Hittinger View (1997) Hittinger (1997) Henricken Brenn, 4000	in management of encodes of encodes of encodes and encoded proceeds.
CENTRAL POWER RESEARCH INSTITUTE		
Switchgear Testing & Development Station Grainfram Illiconf. 21	CENTRAL POWER RESEARCH INSTITUTE	
SUPPLEMENTARY TEST LABORATORY DISPUSIONAL TEST REPORT	CENTRAL FOWER RESEARCH INSTITUTE Swining & Development Station (Gradum) Resol(2)	
est Report No de Date 2007/STL741 A 7 SEP 2007 antomer his reference and address M's Neptune Systems Pvc.Lad.	SUPPLEMENTARY TYST LABORATORY BEDYLEMENTARY TYST LABORATORY	
A-11, Sec-59, Noida, G.B.Nagar,U.P.	Test Report No. & Date : 2010/STL/1281 2 2 NOV 2010	
mafacturer, his reference & address M/s Neptune Systems Pet.Ltd. A-11, Sec.59, Noida, G.B.Nagar,U.P.	Customer bin reference & address : Mis Neptune Systems Put Ltd.	For and on behalf of BSI:
ticulars of apparatus lested 415V, 4000A, LT Switch Board, signation PCC	A-11, Sector - 59, Noida, G.B.Near, (U.P)	
N Neptune Brand nification No./Semple code No. STERST20751457	Menufacturer, his influences & address : Mrs. Neptupe Systems PotLtd.	mulietwan
le. Nil wing. No.(s) 1) NEPCPR101 Sheet 1 of 3 Rev.00	A-11, Soutor - 59, Noida, G.B.Nagar, (U.P)	13.4
 NEPCPRI01 Short 2 of 3 Rev.00 NEPCPRI01 Short 1 of 3 Rev.00 	Particulars of approximates tested : Feeder Distribution Panel (EMPTY)	Managing Director, BSI India, Venkataram Arabolu
of samples tested One	Designation Switch Board. Type Board Distribution Parel (TMPTY)	Originally registered: 15/11/2002 Latest Issue: 13/07/2009 Expiry Date: 14/11/2011
t conducted Verification of temperature rise limits. incluses of test conducted Above tast was conducted at 4000A and the fits obtained were within the limits as specified in the standard and specified by the	identification No. Sample code No. : STDSVL/060775 SUNo. : 690B	
into contained server within the initial as specified in the standard and specified by the some. IIV test was conducted at 2.35V/rms for one minute to check the effect of persitare rise at the adjacent parts of the equipment. The equipment withoutd HV test.	Dataving No.(6)(Utolet revision) : NSPL/NS/102 Rev.00 Sheet 1 of 1 Data (3) of Lot (6) : 18/11/2010 & 19/11/2010	BSI
t in accordance with standard/ IS 8623 (Pant-1), 1993.	No. of samples to ted Test conducted Degree of protection IP-65.	Page: 1 of 2
cifications	Baticulary of test conducted . The abuve test was conducted on the second as	
nomer's requirement/Deviations if any Joints shall be 70 °C declared by the customer	per minukard. No traces of talicum powder observed inside the sample after IPOX net and No incore of worse observed inside the sample after IP X5 net.	
as per standard.	Text in accordance with standard/specification IB: 12047(Part-1), 1993.	
r than Casterner's representative Nil D .	Castomer requirement/Devisitions if any : Nil Name of the Witnessing person	
Her Allalus	Casterner representative : Mr. Prashant Bhardwej, St. Manager, QA	This certificate was issued electronically and remains the property of BSI and is bound by the conditions of contract.
ENGINEER ENGINEERING OFFICER-5	Other than Construer representative : Nil	An electronic certificate can be authenticated onne. Printed copies can be validated at www.big.idplab.com/ClientDirectory or telephone +91 11 2692 9000.
	Marchat 10	Further clastifications regarding the scope of this certificate and the applicability of ISO 9001 2008 requirements may be obtained by consulting the organization. This certificate is valid only if provided onlybaic compared suit
Attended to a second	राज्य विश्वासदाय संयुक्त निवेधक	BSI, The MIRA Corporate Sullies (A-2), Flot 1 and 2, Isthwar Nagar, Mathura Road, New Dethi 110 065.
Sec. 1	Nonce ¹	
Gernadown, BHOPAL-452071	Dia Visita dai valo londra conse universi una di las fantas non ni suana. Persona intervenzione providende las ser supervenzione della data da conse intervenzione della data data data data data data data d	
	20 - yr, - 604 - 8000 600 - 800 - 800 - 800 - 800	

Round the Clock Sales & Service Team all over India



Airport Express





